

# ALUSYNT&REG; MOTOR OIL

□

**Categorie Prodotto:** [Earth-moving](#), [Motors](#), [Oils](#), [Agriculture](#)

## Introduzione

### USES

turbocharged diesel engines in hard service - energy savings

## Descrizione

### SAE - ISO VG - NLGI Gradation

SAE 5W-30, SAE 5W-40, SAE 10W-40, SAE15W-50

Operating temperature &#176;C

Greater than -30

Viscosity index

Greater than 153

## Properties and performance

Synthetic lubricant for commercial vehicles with diesel engines (including turbos) and fixed diesel engines and drives. It is one of the latest specific lubricants for diesel engines and is classified UHPD (Ultra High Performance Diesel). Its viscometric features were designed to offer the ideal viscosity for the latest models of commercial diesel engines. It minimizes wear during ignition, creates energy savings and facilitates cold starts. Also suitable for petrol engines.

## Specifications and fields of use

ACEA: A3/B3/B4/E3/E5/E7. API: C14/CH4/CG4/CF4/CF/CF2/SJ/SL. MB: 228.3 and 229.1. MAN: 3275. VOLVO: VDS-3. CUMMINS: 20076/77/78. MTU: Oil Cat-2. MACK: EO-M Plus. Global: DHD-1. Renault: RLD.